


Glissando POL Slide Scanner

Fast, affordable polarizing slide scanning from Objective Imaging

The new Glissando POL™ polarizing slide scanner from Objective Imaging delivers high quality slide image acquisition in an affordable package. The compact footprint and simple, intuitive user interface make the Glissando POL scanner the ideal platform for quick scanning of geological and birefringent sample microscope slides.

Key Features

- ◆ Excellent price/performance
- ◆ Compact, with removable polarizer
- ◆ Scan one or two 1x2", one or two 1x3" or one 2x3" glass slides
- ◆ Polarized or brightfield slide images
- ◆ 1D and 2D barcode reader
- ◆ Automatic sample detection and focus setup
- ◆ Proven Turboscan™ high performance ultra-fast tile scanning engine
- ◆ All-in-one integrated Windows computer with Ethernet or Wireless connection and HD display monitor
- ◆ Efficient, intuitive software interface
- ◆ Z-Stack polarized slide imaging



Objective Imaging has a worldwide reputation for the innovation and quality of its products. We provide comprehensive and responsive support both directly and through our network of experienced dealers and distributors.

ISO 13485:2003
ISO 9001:2000
FS 76392



Glissando POL Slide Scanner

The Glissando POL Slide Scanner integrates the latest automation technologies and high quality components with our proven Turboscan™ scanning engine to provide an effective, reliable – and affordable – tool for the rapid acquisition of birefringent polarized samples from standard glass 1x2", 1x3" or 2x3" microscope slides.

The easy-to-use Glissando POL software's intuitive design and automated sample detection, focus setup, and barcode reading ensure excellent results, right out of the box.



Specifications

| | |
|--------------------------------|--|
| Slide Capacity | Up to two 25 mm x 75 mm glass slides, or one 50 mm x 75 mm glass slide |
| Scanning Engine | Turboscan™ fast tiling technology with predictive focusing |
| Tissue Detection | Automatic region definition and focus setup |
| Scanning Objective Lens | 10X/0.32 Plan Apo, 20X/0.75 Plan Apo or 40X/0.75 Plan Apo |
| Camera Sensor Size | 2048 x 2048 pixels |
| Sensor Image Resolution | 1.0 µm with 10X lens, 0.5 µm with 20X lens, 0.275 µm with 40X lens |
| Barcode Reader | Image-based 1D and 2D (Datamatrix, QR code) |
| Control Computer | Integral Windows 10 mini-PC with Ethernet and Wireless-N connection |
| On-board Storage | 512GB solid state hard drive |
| Physical Dimensions | 320 mm (W) x 297 mm (H) x 447 mm (D) |
| Electrical | Universal AC input, 50/60 Hz |

Note: Specifications are subject to change without notice



Authorized Dealer:
Meyer Instruments, Inc.
4202 Bear Lodge Court
Houston, TX 77084

281-579-0342
www.meyerinst.com